

## “BIO-BLOCK”



Is a solid, bacteria-laden, organic block for use in degrading organic waste. The safe, naturally occurring bacteria are present in high numbers to handle difficult organic problems. The unique block will gradually dissolve over a 30 to 90 day period or longer which allows for continuous treatment of waste. The naturally occurring bacteria contained in the block will reduce odour, sludge and grease build-up. Bio-Block greatly reduces labour time needed for dosage maintenance. It automates waste water treatment by allowing for 24 hour continuous treatment, not just periodic dosage which also eliminates the need for metering pumps. It breaks down fat and grease build-up, maintains lift station efficiency, significantly reduces odours, is cost effective and easy to use.

**Applications:** Grease traps, pipes, drains, lift stations and anywhere grease or faecal matter is accumulated.

**Directions/Dilutions:** BIO-BLOCK gives round the clock waste degradation treatment with a simple, easy to use system. Simply attach a rope extending from the block. Drop the block into the treatment area. The block will dissolve over a minimum of a 30 day period. May last longer depending on water flow.

### **Laboratory Analysis:**

Appearance: Solid block  
Odour: No odour  
Corrosion: Non corrosive  
Solubility: Water soluble  
Toxicity: Non toxic

Packaging: 2.27 Kg.  
4.55 Kg.



Evaluated and accepted for use in Registered Establishments by the Government of Canada, Canadian Food Inspection Agency.

For further information consult the safety data sheet and label. Visit us at our web site [www.chemfax.com](http://www.chemfax.com)

